

15"

17"

19"

21.5"



### 38,1cm / 15" - 54,6cm / 21.5" Outdoor Monitor Unit with PCAP Touch

Installation from front, optional from rear

#### Description

The outdoor monitor unit with IP65 front in combination with an outdoor monitor meets high requirements, such as readability in daylight, temperature, tightness, vandalism and UV protection. Build the assembly (outdoor monitor unit + outdoor monitor) into a customer front or terminal. The outdoor monitor unit can be screwed to your front from the front. (ALTERNATIVELY - in consultation - the front is provided with holes instead of stud bolts and the installation can be done to your front from the back). The capacitive touch screen is protected against vandalism and equipped with a UV filter. A circumferential sealing tape seals the unit on the front IP65, against water and dust.

Between monitor and touchscreen sensor is a space in which the air can circulate, additional fans prevent stagnant air in the gap.

#### Application Areas

Outdoor and industrial applications requiring IP65 protection, kiosk information systems, self-service and point of information applications.

#### 4 Standard Variants

<b>38,1cm / 15" Outdoor Monitor Unit with PCAP Touch (TIC15.0—XPAU-OUTDOOR)</b>	
<b>43,2cm / 17" Outdoor Monitor Unit with PCAP Touch (TIC17.0—ZPAU-OUTDOOR)</b>	
<b>48,3cm / 19" Outdoor Monitor Unit with PCAP Touch (TIC19.0—ZPAU-OUTDOOR)</b>	
<b>54,6cm / 21.5 Outdoor Monitor Unit with PCAP Touch (TIC21.5—HPAU-OUTDOOR)</b>	
<b>Standard version</b>	<ul style="list-style-type: none"> <li>- front made of brushed stainless steel (V2A)</li> <li>- For installation in existing customer housing (installation from front)</li> <li>- Monitor LED technology with high brightness or transfective backlighting for daylight requirements</li> <li>- Outdoor capable vandalism protected capacitive touch screen, USB</li> <li>- Operating temperature according to outdoor monitor</li> <li>- Rear ventilation system</li> <li>- UV filter</li> <li>- Front IP65 sealed</li> <li>- External power supply</li> </ul>

**Manufacturer warranty: 24 months**

Separately, we offer the outdoor monitor, this allows configurations.

#### Monitor overview

**Customized solutions according to your specifications are already possible at WES from one piece!**

**Technical drawings**

TIC12.1--XPAU-OUTDOOR  
TIC15.0--XPAU-OUTDOOR  
TIC17.0--ZPAU-OUTDOOR  
TIC19.0--ZPAU-OUTDOOR  
TIC21.5--HPAU-OUTDOOR  
TIC24.0--HPAU-OUTDOOR  
Optional  
TIC27.0--HPAU-OUTDOOR

**Note**

The customer must provide adequate protection against excessive humidity, heat and cold. In case of If this is not done, we cannot accept any guarantee. If you want to be on the safe side If you want to be on the safe side, we can alternatively offer you (also customized) complete outdoor terminal solutions.

**Optional**

- Installation from rear, front panel with mounting holes instead of stud bolts
- 12.1" - 24" outdoor monitor units, other sizes on request
- Protective glass instead of touch screen sensor
- RAL color of your choice (powdered surface)

**Alternatively outdoor monitor unit for mounting from the rear to your front with mounting holes, instead of stud bolts.**



We also use the Outdoor Monitor unit in our [Sky Outdoor Terminals](#).



Technical changes and errors excepted. Status: 25.05.2021

**Customized solutions according to your specifications are already possible at WES from one piece!**