



### **Elo Touch Solutions Technical Support**

Online self-help:

www.support.elotouch.com

**North America** 800-ELO-TOUCH Tel +1 408 597 8000 Fax +1 408 597 8050 EloSales.NA@elotouch.com

Europe Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49 elosales@elotouch.com

**Asia-Pacific** Tel +86 (21) 3329 1385 Fax +86 (21) 3329 1400 EloAsia@elotouch.com

## Latin America

Tel 786-923-0251 Fax 305-931-0124 EloSales.LATAM@elotouch.com

The information in this document is subject to change without notice. Elo Touch Solutions, Inc. and its Affiliates (collectively "Elo") makes no representations or warranties with respect to the contents herein, and specifically disclaims any implied warranties of merchantability or fitness for a particular purpose. Elo reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Elo to notify any person of such revisions or changes.

No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, including, but not limited to, electronic, magnetic, optical, chemical, manual, or otherwise without prior written permission of Elo Touch Solutions, Inc.

Elo (logo) and Elo Touch Solutions are trademarks of Elo and its Affiliates.







www.elotouch.com

## **Quick Installation Guide**

NFC Reader

NFC Kit P/N: E001004

Revision B P/N E001010

© 2017 Elo Touch Solutions, Inc. All rights reserved.

# Installation

Please go to www.elotouch.com/support to verify you have the latest drivers before installing this device.




Select the location to mount the NFC Reader. Some systems have more than one mounting option.



Install the 2 flat head screws included with the kit.

Do not adjust the NFC Reader angle without installing the screws or damage may occur.



Remove the selected peripheral cover from the display head to expose the peripheral bay.



Remove the protective film from the included mylar covers and place the covers over the screws.

Adjust the angle as needed.



Gently press the NFC Reader into the peripheral bay making sure the connector is mated.